



New Product Update & Parts Information

Backlapping compounds

The Vapormatic Co. Ltd, PO Box 58, Kestrel Way,
Sowton Industrial Estate, Exeter, EX2 7NB
Tel: +44 (0)1392 684000
Facsimile : +44 (0)1392 438445
Email : marketing@vapormatic.com
Web : www.vapormatic.com

Bulletin	UK	Export	Vap	Issued
1132	Yes	Yes	Yes	24 th April 2007

Vapormatic Backlapping Compounds



Our new and improved, water based Lapping Compounds are ideal for sharpening cylinder mower blades in situ. Depending on the degree of wear and type of equipment the correct grade is available from fine to coarse. A stable, easy-to-use fluid which has low environmental impact and excellent value for money.

- New Improved Formula
- Now Twice As Much Grit
- Washes Off Easily
- Low 'fling' formula
- Anti-corrosion Agent To Stop Rusting
- Oil Free
- Low odour
- Improves Cutting Performance
- Immediate results
- Suitable for most types of equipment

Part Number	Description
VLB4250	80 Grit, 4.5kg
VLB4251	80 Grit, 10kg
VLB4252	120 Grit, 4.5kg
VLB4253	120 Grit, 10kg
VLB4254	180 Grit, 4.5kg
VLB4255	180 Grit, 10kg
VLB4256	220 Grit, 4.5kg
VLB4257	220 Grit, 10kg

Application

Please refer to your machine operators manual to ensure correct application as instructions may vary between cylinder designs.

General application

Adjust cutting edges to be level and within 1mm of each other and coat blades with compound using swab or brush. This can be done whilst the blades are running in reverse lapping gear but obvious safety precautions should be taken. The selection of coarse, medium or fine will depend upon type of equipment and degree of sharpening needed. Run machine without cutting grass for up to 1 minute and re-apply if necessary. Re-adjust blades accordingly.

Vapormatic - The Genuine Alternative

Original equipment manufacturers names and part number are quoted for reference purposes only and are not intended to infer that our replacement parts are used as original equipment.