



New Product Update & Parts Information

PTO Equipment

The Vapormatic Co. Ltd, PO Box 58, Kestrel Way,
Sowton Industrial Estate, Exeter, EX2 7NB
Tel: +44 (0)1392 684000
Facsimile : +44 (0)1392 438445
Email : marketing@vapormatic.com
Web : www.vapormatic.com

| Bulletin | UK | Export | Vap | Issued |
|----------|-----|--------|-----|------------------------------|
| 1141 | Yes | Yes | Yes | 15 th August 2007 |

Double Wide Angle PTO

We are delighted to announce that now available in stock is a new addition to our PTO range. With an 80° wide angle UJ at **each end** this VTE1178 PTO shaft gives you the best possible turning circle and manoeuvrability. For added safety a quick release collar is provided at both ends.



VTE1178

| | |
|---------------------------------|----------------------|
| Minimum joint centre length | 1210 mm (47.638 in) |
| Tractor end fitting | QR 1 3/8", 6 |
| Implement end fitting | QR 1 3/8", 6 |
| Maximum joint centre length | 1690 mm (66.535 in) |
| Profile | Lemon 1bGA - 2a |
| Series | WWE2480 |
| 540rpm power and torque rating | 66kW (1175Nm) |
| 1000rpm power and torque rating | 61kW (580Nm) |
| UJ Size | 32 x 76 x 27 x 98 mm |

All PTO drive shafts manufactured by BENZI & DI TERLIZZI and supplied by VAPORMATIC fully conform to the Machinery Directive 89/392 linked to European Safety Norms EN292, EN294, EN1152 as well as the recent EN12965. In particular the shafts satisfy the need of European Safety Norm EN12965:2004, that all primary (original equipment) PTO drive shafts must be equipped with a PTO yoke on the Tractor side, featuring "a locking device that shall have no point which can cause entanglement (e.g. by collar design)."

Vapormatic – The Genuine Alternative

Original equipment manufacturers names and part number are quoted for reference purposes only and are not intended to infer that our replacement parts are used as original equipment.